PKCS #7:
Cryptographic Message Syntax Standard

RSA Data Security, Inc.
Redwood City, CA

June 3, 1991

Version 1.4[1]

1. Scope

This standard describes a general syntax for data that may have cryptography applied to it, such as digital signatures and digital envelopes. The syntax admits recursion, so that, for example, one envelope can be nested inside another, or one party can sign some previously enveloped digital data. It also allows arbitrary attributes, such as signing time, to be authenticated along with the content of a message, and provides for other attributes such as countersignatures to be associated with a signature.

This standard is compatible with Privacy-Enhanced Mail (PEM) [1] in that signed-data and signed-and-enveloped-data content, constructed in a PEM-compatible mode, can be converted into PEM messages without any cryptographic operations. PEM messages can similarly be converted into the signed-data and signed-and-enveloped data content types.

This standard can support a variety of architectures for certificate-based key management, such as the one proposed for Privacy-Enhanced Mail in RFC 1114 [2]. Architectural decisions such as what certificate issuers are considered "top-level," what entities certificate issuers are authorized to certify, and what distinguished names are considered acceptable are left outside the standard. Dissemination of "hot lists" of invalid certificates (certificate-revocation lists) is also left outside.

The values produced according to this standard are intended to be BER-encoded [3], which means that the values would would typically be represented as octet strings. While many systems are capable of transmitting arbitrary octet strings reliably, it is well known that many electronic-mail systems are not. This standard does not address mechanisms for encoding octet strings as (say) strings of ASCII characters or other techniques for

---

[1]Versions 1.0–1.3 are superseded by this version. The earlier versions were distributed to participants in RSA Data Security, Inc.'s Public-Key Cryptography Standards meetings in February and March 1991.

enabling reliable transmission by re-encoding the octet string. RFC 1113 [1] suggests one possible solution to this problem.

2. References

[1] J. Linn. *RFC 1113: Privacy Enhancement for Internet Electronic Mail: Part I -- Message Encipherment and Authentication Procedures.* August 1989. See also [17].

[2] S. Kent and J. Linn. *RFC [1114]: Privacy Enhancement for Internet Electronic Mail: Part II -- Certificate-Based Key Management.* August 1989. See also [15].

[3] CCITT. *Recommendation X.209: Specification of Basic Encoding Rules for Abstract Syntax Notation One (ASN.1).* 1988.

[4] CCITT. *Recommendation X.509: The Directory—Authentication Framework.* 1988.

[5] CCITT. *Recommendation X.208: Specification of Abstract Syntax Notation One (ASN.1).* 1988.

[6] CCITT. *Recommendation X.501: The Directory—Models.* 1988.

[7] RSA Data Security, Inc. *PKCS #6: Extended-Certificate Syntax Standard.* Version 1.4, June 1991.

[8] CCITT. *Recommendation X.500: The Directory—Overview of Concepts, Models and Services.* 1988.

[9] National Bureau of Standards. *FIPS Publication 46-1: Data Encryption Standard.* January 1988.

[10] J. Linn. *RFC 1115: Privacy Enhancement for Internet Electronic Mail: Part III -- Algorithms, Modes, and Identifiers.* August 1989.

[11] B.S. Kaliski Jr. *RFC [MD2]: The MD2 Message-Digest Algorithm.* Draft, April 1991.

[12] Ronald L. Rivest and Stephen R. Dusse. *RFC [MD5]: The MD5 Message-Digest Algorithm.* In preparation.

[13] NIST. *Special Publication 500-183: Stable Implementation Agreements for Open Systems Interconnection Protocols.* Version 4, Edition 1, Part 11, December 1990.

[14] RSA Data Security, Inc. *PKCS #1: RSA Encryption Standard.* Version 1.4, June 1991.

[15] S. Kent. *RFC [1114B]: Privacy Enhancement for Internet Electronic Mail: Part II: Certificate-Based Key Management.* Draft, February 1991.

[16] RSA Data Security, Inc. *PKCS #9: Selected Attribute Types.* Version 10., June 1991.

[17] J. Linn. *[RFC 1113D]: Privacy Enhancement for Internet Electronic Mail: Part I: Message Encryption and Authentication Procedures.* Internet draft, March 1991.

3. Definitions

For the purposes of this standard, the following definitions apply.

`AlgorithmIdentifier`: A type that identifies an algorithm (by object identifier) and associated parameters. This type is defined in X.509 [4].

ASN.1: Abstract Syntax Notation One, as defined in X.208 [5].

`Attribute`: A type that contains an attribute type (specified by object identifier) and one or more attribute values. This type is defined in X.501 [6].

BER: Basic Encoding Rules, as defined in X.209 [3].

`Certificate`: A type that binds an entity's distinguished name to a public key with a digital signature. This type is defined in X.509 [4] as revised by RFC 1114 [2]. This type also contains the distinguished name of the certificate issuer (the signer), an issuer-specific serial number, the issuer's signature algorithm identifier, and a validity period. Throughout this standard, the term "X.509 certificate" refers to the revised syntax in RFC 1114.

`CertificateSerialNumber`: A type that uniquely identifies a certificate (and thereby an entity and a public key) among those signed by a particular certificate issuer. This type is defined in RFC 1114 [2].

DER: Distinguished Encoding Rules for ASN.1, as defined in X.509, Section 8.7.

`ExtendedCertificate`: An type that consists of consists of an X.509 public-key certificate and a set of attributes, collectively signed by the issuer of the X.509 public-key certificate. This type is defined in PKCS #6 [7].

`Name`: A type that uniquely identifies or "distinguishes" objects in a X.500 directory [8]. This type is defined in X.501. In an X.509 certificate, the type identifies the certificate issuer and the entity whose public key is certified.

4. Symbols and abbreviations

Upper-case italic symbols (e.g., *MD*) denote octet strings. Underlining (e.g., *MDO*) indicates that an octet string is BER-encoded.

MD message digest

MDO BER-encoded message-digest object identifier

5. General overview

The following eight sections specify useful types, general syntax, five content types, and object identifiers.

The syntax is general enough to support many different content types. This standard defines five: data, signed data, enveloped data, signed-and-enveloped data, and digested data. Other content types may be added in the future. The use of content types defined outside this standard is possible, but is subject to bilateral agreement between parties exchanging content.

This standard exports one type, `ContentInfo`, as well as the various object identifiers.

There are two classes of content types: base and enhanced. Content types in the base class contain "just data," with no cryptographic enhancements. Presently, one content type is in this class, the data content type. Content types in the enhanced class contain content of some type (possibly encrypted), and other cryptographic enhancements. For example, enveloped-data content can contain (encrypted) signed-data content, which can contain data content. The four non-data content types fall into the enhanced class. The content types in the enhanced class thus employ encapsulation, giving rise to the terms "outer" content (the one containing the enhancements) and "inner" content (the one being enhanced).

The standard is designed such that the enhanced content types can be prepared and processed in a single pass. Single-pass operation is especially helpful if content is stored on tapes, or is "piped" from another process. One of the drawbacks of single-pass operation, however, is that it is difficult to output a DER encoding in a single pass, since the lengths of the various components may not be known in advance. Since DER encoding is required by the signed-data, signed-and-enveloped data, and digested-data content types, an extra pass may be necessary when a content type other than data is the inner content of one of those content types.

6. Useful types

This section defines types that are useful in at least two places in the standard.

6.1 ContentEncryptionAlgorithmIdentifier

The `ContentEncryptionAlgorithmIdentifier` type identifies a content-encryption algorithm such as DES [9].

```
ContentEncryptionAlgorithmIdentifier ::= AlgorithmIdentifier
```

6.2 DigestAlgorithmIdentifier

The `DigestAlgorithmIdentifier` type identifies a message-digest algorithm. Examples include MD2 [10,11] and MD5 [12], whose object identifiers are given in the NIST/OIW agreements [13].

```
DigestAlgorithmIdentifier ::= AlgorithmIdentifier
```

6.3 DigestEncryptionAlgorithm

The `DigestEncryptionAlgorithm` type identifies a digest-encryption algorithm under which a message digest can be encrypted. One example is PKCS #1's `rsaEncryption` [14].

```
DigestEncryptionAlgorithmIdentifier ::= AlgorithmIdentifier
```

6.4 ExtendedCertificateOrCertificate

The `ExtendedCertificateOrCertificate` type gives either a PKCS #6 extended certificate [7] or an X.509/RFC 1114 certificate [4,2]. This type follows the syntax recommended in Section 6 of PKCS #6:

```
ExtendedCertificateOrCertificate ::= CHOICE {
  certificate Certificate, -- X.509/RFC 1114 certificate
  extendedCertificate [0] IMPLICIT ExtendedCertificate }
```

6.5 ExtendedCertificatesAndCertificates

The `ExtendedCertificatesAndCertificates` type gives a set of extended certificates and X.509 certificates. It is intended that the set be sufficient to contain chains from a recognized "root" or "top-level certification authority" to all of the signers with which the set is associated, but there may be more certificates than necessary, or there may be fewer than necessary.

```
ExtendedCertificatesAndCertificates ::=
  SET OF ExtendedCertificateOrCertificate
```

Note. The precise meaning of a "chain" is outside the scope of this standard. Some applications of this standard may impose upper limits on the length of a chain; others may enforce certain relationships between the subjects and issuers of certificates in a chain. An example of such relationships has been proposed for Privacy-Enhanced Mail in RFCs 1114 [2] and [1114B] [17].

6.6 IssuerAndSerialNumber

The `IssuerAndSerialNumber` type identifies a certificate (and thereby an entity and a public key) by the distinguished name of the certificate issuer and an issuer-specific certificate serial number.

```
IssuerAndSerialNumber ::= SEQUENCE {
  issuer Name,
  serialNumber CertificateSerialNumber }
```

6.7 KeyEncryptionAlgorithmIdentifier

The `KeyEncryptionAlgorithmIdentifier` type identifies a key-encryption algorithm under which a content-encryption key can be encrypted. One example is PKCS #1's `rsaEncryption`.

```
KeyEncryptionAlgorithmIdentifier ::= AlgorithmIdentifier
```

6.8 Version

The `Version` type gives a syntax version number, for compatibility with future revisions of this standard.

```
Version ::= INTEGER
```

7. General syntax

The general syntax for content exchanged between entities according to this standard associates a content type with content. The syntax shall have ASN.1 type `ContentInfo`:

```
ContentInfo ::= SEQUENCE {
  contentType ContentType,
  content [0] EXPLICIT ANY DEFINED BY contentType OPTIONAL }

ContentType ::= OBJECT IDENTIFIER
```

The fields of type `ContentInfo` have the following meanings:

- `contentType` indicates the type of content. It is an object identifier, which means it is a unique string of integers assigned by the authority that defines the content type. This standard defines five content types (see

Section 13): `data`, `signedData`, `envelopedData`, `signed-AndEnvelopedData`, and `digestedData`.

- `content` is the content. The field is optional, and if the field is not present, its intended value must be supplied by other means. Its type is defined along with the object identifier for `contentType`.

Notes.

1. The methods below assume that the type of `content` can be determined uniquely by `contentType`, so the type defined along with the object identifier should not be a `CHOICE` type.

2. When a `ContentInfo` value is the inner content of signed-data, signed-and-enveloped-data, or digested-data content, a message-digest algorithm is applied to the contents octets of the DER encoding of the `content` field. When a `ContentInfo` value is the inner content of enveloped-data or signed-and-enveloped-data content, a content-encryption algorithm is applied to the contents octets of a definite-length BER encoding of the `content` field.

3. The optional omission of the `content` field makes it possible to construct "external signatures," for example, without modification to or replication of the content to which the signatures apply. In the case of external signatures, the content being signed would be omitted from the "inner" encapsulated `ContentInfo` value included in the signed-data content type.

8. Data content type

The data content type is just an octet string. It shall have ASN.1 type `Data`:

```
Data ::= OCTET STRING
```

The data content type is intended to refer to arbitrary octet strings, such as ASCII text files. Such strings need not have any internal structure (although they may; they could even be DER encodings).

9. Signed data content type

The signed-data content type consists of content of any type and encrypted message digests of the content for one or more signers. The combination of content and encrypted digest for a signer is a "digital signature" for that signer. Any type of content can be signed by any number of signers in parallel.

It is expected that the typical application of the signed-data content type will be to represent one signer's digital signature on content of the data content type.

The process by which signed data is constructed involves the following steps:

1. For each signer, a message digest is computed on the content with a signer-specific message-digest algorithm. (If two signers employ the same message-digest algorithm, then the message digest need be computed for only one of them.) If the signer is authenticating any information other than the content (see Section 9.2), the message digest of the content and the other information are digested with the signer's message digest algorithm, and the result becomes the "message digest."

2. For each signer, the message digest and associated information are encrypted with the signer's private key.

3. For each signer, the encrypted message digest and other signer-specific information are collected into a `SignerInfo` value, defined in Section 9.2.

4. The message-digest algorithms for all the signers and the `SignerInfo` values for all the signers are collected together with the content into a `SignedData` value, defined in Section 9.1.

The process is reversed (i.e., signatures are verified) by decrypting the encrypted message digest for each signer with the signer's public key, then comparing the recovered message digest to an independently computed message digest. The signer's public key is either contained in a certificate included in the signer information, or is referenced by an issuer distinguished name and an issuer-specific serial number that uniquely identify the certificate for the public key.

This section is divided into five parts. The first part describes the top-level type `SignedData`, the second part describes the per-signer information type `SignerInfo`, and the third and fourth parts describe the message-digesting and digest-encryption processes. The fifth part summarizes compatibility with Privacy-Enhanced Mail.

9.1 SignedData type

The signed-data content type shall have ASN.1 type `SignedData`:

```
SignedData ::= SEQUENCE {
  version Version,
  digestAlgorithms DigestAlgorithmIdentifiers,
  contentInfo ContentInfo,
  certificates
    [0] IMPLICIT ExtendedCertificatesAndCertificates
```

```
      OPTIONAL,
  signerInfos SignerInfos }

DigestAlgorithmIdentifiers ::=
  SET OF DigestAlgorithmIdentifier

SignerInfos ::= SET OF SignerInfo
```

The fields of type `SignedData` have the following meanings:

- `version` is the syntax version number. It shall be 0 for this version of the standard.
- `digestAlgorithms` is a collection of message-digest algorithm identifiers. There must be at least one element in the collection. Each element identifies the message-digest algorithm (and any associated parameters) under which the content is digested for a some signer. The collection is intended to list the message-digest algorithms employed by all of the signers, in any order, to facilitate one-pass signature verification. The message-digesting process is described in Section 9.3.
- `contentInfo` is the content that is signed. It can be in any of the defined content types.
- `certificates` is a set of PKCS #6 extended certificates and X.509 certificates. It is intended that the set be sufficient to contain chains from a recognized "root" or "top-level certification authority" to all of the signers in the `signerInfos` field. There may be more certificates than necessary, and there may be certificates sufficient to contain chains from two or more independent top-level certification authorities. There may also be fewer certificates than necessary, if it is expected that those verifying the signatures have an alternate means of obtaining necessary certificates (e.g., from a previous set of extended certificates).
- `signerInfos` is a collection of per-signer information. There must be at least one element in the collection.

Note. The fact that the `digestAlgorithms` field comes before the `contentInfo` field and the `signerInfos` field comes after it makes it possible to process a `SignedData` value in a single pass. (Single-pass processing is described in Section 5.)

9.2 SignerInfo type

Per-signer information is represented in the type `SignerInfo`:

```
SignerInfo ::= SEQUENCE {
  version Version,
  issuerAndSerialNumber IssuerAndSerialNumber,
  digestAlgorithm DigestAlgorithmIdentifier,
  authenticatedAttributes [0] IMPLICIT Attributes OPTIONAL,
  digestEncryptionAlgorithm
                        DigestEncryptionAlgorithmIdentifier,
  encryptedDigest EncryptedDigest,
  unauthenticatedAttributes [1] IMPLICIT Attributes OPTIONAL
}

EncryptedDigest ::= OCTET STRING
```

The fields of type `SignerInfo` have the following meanings:

- `version` is the syntax version number. It shall be 0 for this version of the standard.

- `issuerAndSerialNumber` specifies the signer's certificate (and thereby the signer's distinguished name and public key) by issuer distinguished name and issuer-specific serial number.

- `digestAlgorithm` identifies the message-digest algorithm (and any associated parameters) under which the content and authenticated attributes (if present) are digested. The message-digesting process is described in Section 9.3.

- `authenticatedAttributes` is a set of attributes that are signed (i.e., authenticated) by the signer. The field is optional, but it must be present if either the content type of the `ContentInfo` value being signed is not `data`, or the associated parameters of the message-digest algorithm are not `NULL`. If the field is present, it must contain, at a minimum, two attributes:

    1. A content-type attribute having as its value the content type of the `ContentInfo` value being signed.

    2. A message-digest attribute, having as its value the message digest of the content (see below).

  These attributes are defined in Section 7 of PKCS #9 [16]. Other attribute types that might be useful here, such as signing time, are also defined in PKCS #9.

- `digestEncryptionAlgorithm` identifies the digest-encryption algorithm (and any associated parameters) under which the message digest

and associated information are encrypted with the signer's private key. The digest-encryption process is described in Section 9.4.

- `encryptedDigest` is the result of encrypting the message digest and associated information with the signer's private key.

- `unauthenticatedAttributes` is a set of attributes that are not signed (i.e., authenticated) by the signer. The field is optional. Attribute types that might be useful here, such as countersignatures, are defined in PKCS #9.

Note. It is recommended in the interest of PEM compatibility that the `authenticatedAttributes` field be omitted whenever the content type of the `ContentInfo` value being signed is `data`, the associated parameters of the message-digest algorithm are `NULL`, and there are no other authenticated attributes.

9.3 Message-digesting process

The message-digesting process computes a message digest on either the content being signed or the content together with the signer's authenticated attributes. In either case, the initial input to the message-digesting process is the "value" of the content being signed. Specifically, the initial input is the contents octets of the DER encoding of the `content` field of the `ContentInfo` value to which the signing process is applied. Only the contents octets of the DER encoding of that field are digested, not the identifier octets or the length octets.

The result of the message-digesting process (which is called, informally, the "message digest") depends on whether the `authenticatedAttributes` field is present. When the field is absent, the result is just the message digest of the content. When the field is present, however, the result is the message digest of the complete DER encoding of the `authenticatedAttributes` field. Since the field when present must contain as attributes the content type and the message digest of the content, those values are indirectly included in the result.

When the content being signed has content type `data` and the `authenticatedAttributes` field is absent, then just the value of the data (e.g., the contents of a file) is digested. This has the advantage that the length of the content being signed need not be known in advance of the encryption process. This method is compatible with Privacy-Enhanced Mail.

Although the identifier octets and the length octets are not digested, they are still protected by other means. The length octets are protected by the nature of the message-digest algorithm since it is by assumption computationally infeasible to find any two distinct messages of any length that have the same message digest. Furthermore, assuming that the content type uniquely determines the identifier octets, the identifier

octets are protected implicitly in one of two ways: either by the inclusion of the content type in the authenticated attributes, or by the use of the PEM-compatible alternative in Section 9.4 which implies that the content-type is `data`.

Note. The fact that the message digest is computed on part of a DER encoding does not mean that DER is the required method of representing that part for data transfer. Indeed, it is expected that some implementations of this standard may store objects in other than their DER encodings, but such practices do not affect message-digest computation.

9.4 Digest-encryption process

The input to the digest-encryption process—the value supplied to the signer's digest-encryption algorithm—includes the result of the message-digesting process (informally, the "message digest") and the digest algorithm identifier (or object identifier). The result of the digest-encryption process depends on whether the `authenticatedAttributes` field is present; there are two alternatives.

9.4.1 Alternative 1: authenticatedAttributes field is present

When the `authenticatedAttributes` field is present, the result is the encryption with the signer's private key of the BER encoding of a value of type `DigestInfo`:

```
DigestInfo ::= SEQUENCE {
  digestAlgorithm DigestAlgorithmIdentifier,
  digest Digest }

Digest ::= OCTET STRING
```

The fields of type `DigestInfo` have the following meanings:

- `digestAlgorithm` identifies the message-digest algorithm (and any associated parameters) under which the content and authenticated attributes are digested. It should be the same as the `digestAlgorithm` field of the superior `SignerInfo` value.
- `digest` is the result of the message-digesting process.

9.4.2 Alternative 2: authenticatedAttributes field is absent

When the `authenticatedAttributes` field is absent, the result is the encryption with the signer's private key of an octet string of the form

MDO || *MD*

where

- *MDO* is the DER encoding of the `OBJECT IDENTIFIER` value that identifies the message-digest algorithm under which the content is digested. It should be the same as the object identifier specified in the `digestAlgorithm` field of the superior `SignerInfo` value.

- *MD* is the result of the message-digesting process.

This alternative is intended for Privacy-Enhanced Mail compatibility.

Notes.

1. The values resulting from the two alternatives are easily distinguished since the first octet of *MDO* is always `06` and the first octet of the DER encoding of the `DigestInfo` value is always `30`.

2. The input to the encryption process typically will have 30 or fewer octets. If `digestEncryptionAlgorithm` is PKCS #1's `rsaEncryption` [14], then this means that the input can be encrypted in a single block as long as the length of the RSA modulus is at least 328 bits, which is reasonable and consistent with security recommendations.

3. A message-digest algorithm identifier is included in the `DigestInfo` value to limit the damage resulting from the compromise of one message-digest algorithm. For instance, suppose an adversary were able to find messages with a given MD2 message digest. That adversary might try to forge a signature on a message by finding an innocuous-looking message with the same MD2 message digest, and coercing a signer to sign the innocuous-looking message. This attack would succeed only if the signer used MD2. If the `DigestInfo` value contained only the message digest, however, an adversary could attack signers that use any message digest.

9.5 Compatibility with Privacy-Enhanced Mail

Compatibility with the `MIC-ONLY` and `MIC-CLEAR` process types in PEM occurs when the content type of the `ContentInfo` value being signed is `data`, there are no authenticated attributes, the message-digest algorithm is NIST/OIW's `md2` or `md5`[2] [13], and the digest-encryption algorithm is PKCS #1's `rsaEncryption` [14]. Under all those conditions, the encrypted message digest produced here matches the one produced in PEM because:

---

[2]Not yet registered.

1. The value input to the message-digest algorithm in PEM is the same as in this standard when there are no authenticated attributes. MD2 and MD5 in PEM are the same as NIST/OIW's `md2` and `md5`.

2. The value encrypted with the signer's private key in PEM is the same as in this standard when there are no authenticated attributes (see Section 9.4.2). RSA private-key encryption in PEM is the same as PKCS #1's `rsaEncryption`.

The other parts of the signed-data content type (certificates, algorithm identifiers, etc.) are easily translated to and from their corresponding PEM components.

10. Enveloped data content type

The enveloped-data content type consists of encrypted content of any type and encrypted content-encryption keys for one or more recipients. The combination of encrypted content and encrypted content-encryption key for a recipient is a "digital envelope" for that recipient. Any type of content can be enveloped for any number of recipients in parallel.

It is expected that the typical application of the enveloped-data content type will be to represent one or more recipients' digital envelopes on content of the data, digested-data, or signed-data content types.

The process by which enveloped data is constructed involves the following steps:

1. A content-encryption key for a particular content-encryption algorithm is generated at random.

2. For each recipient, the content-encryption key is encrypted with the recipient's public key.

3. For each recipient, the encrypted content-encryption key and other recipient-specific information are collected into a `RecipientInfo` value, defined in Section 10.2.

4. The content is encrypted with the content-encryption key. (Content encryption may require that the content be padded to a multiple of some block size, but any padding is left to the content-encryption algorithm.)

5. The `RecipientInfo` values for all the recipients are collected together with the encrypted content into a `EnvelopedData` value, defined in Section 10.1.

The process is reversed (i.e., envelopes are opened) by decrypting the encrypted content-encryption key for some recipient with the recipient's private key and decrypting the en-

crypted content with the recovered content-encryption key. The recipient's private key is referenced by an issuer distinguished name and an issuer-specific serial number that uniquely identify the certificate for the corresponding public key.

This section is divided into four parts. The first part describes the top-level type `EnvelopedData`, the second part describes the per-recipient information type `RecipientInfo`, and the third and fourth parts describe the content-encryption and key-encryption processes.

This content type is not compatible with Privacy-Enhanced Mail (although some processes it defines are compatible with their PEM counterparts), since Privacy-Enhanced Mail always involves digital signatures, never digital envelopes alone.

10.1 EnvelopedData type

The enveloped-data content type shall have ASN.1 type `EnvelopedData`:

```
EnvelopedData ::= SEQUENCE {
  version Version,
  recipientInfos RecipientInfos,
  encryptedContentInfo EncryptedContentInfo }

RecipientInfos ::= SET OF RecipientInfo

EncryptedContentInfo ::= SEQUENCE {
  contentType ContentType,
  contentEncryptionAlgorithm
                       ContentEncryptionAlgorithmIdentifier,
  encryptedContent [0] IMPLICIT EncryptedContent OPTIONAL }

EncryptedContent ::= OCTET STRING
```

The fields of type `EnvelopedData` have the following meanings:

- `version` is the syntax version number. It shall be 0 for this version of the standard.
- `recipientInfos` is a collection of per-recipient information. There must be at least one element in the collection.
- `encryptedContentInfo` is the encrypted content information.

The fields of type `EncryptedContentInfo` have the following meanings:

- `contentType` indicates the type of content.

- `contentEncryptionAlgorithm` identifies the content-encryption algorithm (and any associated parameters) under which the content is encrypted. The content-encryption process is described in Section 10.3. This algorithm is the same for all recipients.

- `encryptedContent` is the result of encrypting the content. The field is optional, and if the field is not present, its intended value must be supplied by other means.

Note. The fact that the `recipientInfos` field comes before the `encrypted-ContentInfo` field makes it possible to process an `EnvelopedData` value in a single pass. (Single-pass processing is described in Section 5.)

10.2 RecipientInfo type

Per-recipient information is represented in the type `RecipientInfo`:

```
RecipientInfo ::= SEQUENCE {
  version Version,
  issuerAndSerialNumber IssuerAndSerialNumber,
  keyEncryptionAlgorithm KeyEncryptionAlgorithmIdentifier,
  encryptedKey EncryptedKey }

EncryptedKey ::= OCTET STRING
```

The fields of type `RecipientInfo` have the following meanings:

- `version` is the syntax version number. It shall be 0 for this version of the standard.

- `issuerAndSerialNumber` specifies the recipient's certificate (and thereby the recipient's distinguished name and public key) by issuer distinguished name and issuer-specific serial number.

- `keyEncryptionAlgorithm` identifies the key-encryption algorithm (and any associated parameters) under which the content-encryption key is encrypted with the recipient's public key. The key-encryption process is described in Section 10.4.

- `encryptedKey` is the result of encrypting the content-encryption key with the recipient's public key (see below).

10.3 Content-encryption process

The input to the content-encryption process is the "value" of the content being enveloped. Specifically, the input is the contents octets of a definite-length BER encoding of the `content` field of the `ContentInfo` value to which the enveloping process is applied. Only the contents octets of the BER encoding are encrypted, not the identifier octets or length octets; those other octets are not represented at all.

When the content being enveloped has content type `data`, then just the value of the data (e.g., the contents of a file) is encrypted. This has the advantage that the length of the content being signed need not be known in advance of the encryption process. This method is compatible with Privacy-Enhanced Mail.

The identifier octets and the length octets are not encrypted. The length octets may be protected implicitly by the encryption process, depending on the encryption algorithm. The identifier octets are not protected at all, although they can be recovered from the content type, assuming that the content type uniquely determines the identifier octets. Explicit protection of the identifier and length octets requires that the signed-and-enveloped-data content type be employed, or that the digested-data and enveloped-data content types be applied in succession.

Note. The reason that a definite-length BER encoding is required is that the bit indicating whether the length is definite or indefinite is not recorded anywhere in the enveloped-data content type. Definite-length encoding is more appropriate for simple types such as octet strings, so definite-length encoding is chosen.

10.4 Key-encryption process

The input to the key-encryption process—the value supplied to the recipient's key-encryption algorithm—is just the "value" of the content-encryption key.

11. Signed-and-enveloped data content type

This section defines the signed-and-enveloped data content type. For brevity, much of this section is expressed in terms of material in Sections 9 and 10.

The signed-and-enveloped-data content type consists of encrypted content of any type, encrypted content-encryption keys for one or more recipients, and doubly encrypted message digests for one or more signers. The "double encryption" consists of an encryption with a signer's private key followed by an encryption with the content-encryption key.

The combination of encrypted content and encrypted content-encryption key for a recipient is a "digital envelope" for that recipient. Similarly, the combination of recovered

content and recovered singly-encrypted message digest for a signer is a "digital signature" for that signer. Any type of content can be enveloped for any number of recipients and signed by any number of signers in parallel.

It is expected that the typical application of the signed-and-enveloped-data content type will be to represent one signer's digital signature and one or more recipients' digital envelopes on content of the data content type.

The process by which signed-and-enveloped data is constructed involves the following steps:

1. A content-encryption key for a particular content-encryption algorithm is generated at random.

2. For each recipient, the content-encryption key is encrypted with the recipient's public key.

3. For each recipient, the encrypted content-encryption key and other recipient-specific information are collected into a `RecipientInfo` value, defined in Section 10.2.

4. For each signer, a message digest is computed on the content with a signer-specific message-digest algorithm. (If two signers employ the same message-digest algorithm, then the message digest need be computed for only one of them.)

5. For each signer, the message digest and associated information are encrypted with the signer's private key, and the result is encrypted with the content-encryption key. (The second encryption may require that the result of the first encryption be padded to a multiple of some block size, but any padding is left to the content-encryption algorithm.)

6. For each signer, the doubly encrypted message digest and other signer-specific information are collected into a `SignerInfo` value, defined in Section 9.2.

7. The content is encrypted with the content-encryption key. (Again, any padding is left to the content-encryption algorithm.)

8. The message-digest algorithms for all the signers, the `SignerInfo` values for all the signers and the `RecipientInfo` values for all the recipients are collected together with the encrypted content into a `SignedAndEnvelopedData` value, defined in Section 11.1.

The process is reversed (i.e., envelopes are opened and signatures are verified) in two steps. First, the encrypted content-encryption key for some recipient is decrypted with the recipient's private key, and the encrypted content is decrypted with the recovered

content-encryption key. Second, the doubly encrypted message digest for each signer is decrypted with the recovered content-encryption key, the result is decrypted with the signer's public key, and the recovered message digest is compared to an independently computed message digest.

Recipient private keys and signer public keys are contained or referenced as discussed in Sections 9 and 10.

This section is divided into three parts. The first part describes the top-level type `SignedAndEnvelopedData` and the second part describes the digest-encryption process. Other types and processes are the same as in Sections 9 and 10. The third part summarizes compatibility with Privacy-Enhanced Mail.

Note. The signed-and-enveloped-data content type provides cryptographic enhancements similar to those resulting from the sequential combination of signed-data and enveloped-data content types. However, since the signed-and-enveloped-data content type does not have authenticated or unauthenticated attributes, nor does it provide enveloping of signer information other than the signature, the sequential combination of signed-data and enveloped-data content types is generally preferable to the `SignedAndEnvelopedData` content type, except when compatibility with the `ENCRYPTED` process type in Privacy-Enhanced Mail in intended.

11.1 SignedAndEnvelopedData type

The signed-and-enveloped-data content type shall have ASN.1 type `SignedAndEnvelopedData`:

```
SignedAndEnvelopedData ::= SEQUENCE {
  version Version,
  recipientInfos RecipientInfos,
  digestAlgorithms DigestAlgorithmIdentifiers,
  encryptedContentInfo EncryptedContentInfo,
  extendedCertificates
                [0] IMPLICIT ExtendedCertificates OPTIONAL,
  signerInfos SignerInfos }
```

The fields of type `SignedAndEnvelopedData` have the following meanings:

- `version` is the syntax version number. It shall be 0 for this version of the standard.

- `recipientInfos` is a collection of per-recipient information, as in Section 10. There must be at least one element in the collection.

- `digestAlgorithms` is a collection of message-digest algorithm identifiers, as in Section 9. The message-digesting process is the same as in Section 9 in the case when there are no authenticated attributes.

- `encryptedContentInfo` is the encrypted content, as in Section 10. It can be in any of the defined content types.

- `certificates` is a set of PKCS #6 extended certificates and X.509 certificates, as in Section 9.

- `signerInfos` is a collection of per-signer information. There must be at least one element in the collection. `SignerInfo` values have the same meaning as in Section 9 with the exception of the `encryptedDigest` field (see below).

Note. The fact that the `recipientInfos` and `digestAlgorithms` fields come before the `contentInfo` field and the `signerInfos` field comes after it makes it possible to process a `SignedAndEnvelopedData` value in a single pass. (Single-pass processing is described in Section 5.)

11.2 Digest-encryption process

The input to the digest-encryption process is the same as in Section 9, but the process itself is different. Specifically, the process involves two steps. First, the input to the process is supplied to the signer's digest-encryption algorithm, as in Section 9. Second, the result of the first step is encrypted with the content-encryption key. There is no DER encoding between the two steps; the "value" output by the first step is input directly to the second step. (As usual, any padding is left to the content-encryption algorithm.)

This process is compatible with the `ENCRYPTED` process type in Privacy-Enhanced Mail.

Note. The purpose of the second step is to prevent an adversary from recovering the message digest of the content. Otherwise, an adversary would be able to determine which of a list of candidate contents (e.g., "Yes" or "No") is the actual content by comparing the their message digests to the actual message digest.

11.3 Compatibility with Privacy-Enhanced Mail

Compatibility with the `ENCRYPTED` process type of PEM occurs when the content type of the `ContentInfo` value being signed and enveloped is `data`, the message-digest

algorithm is NIST/OIW's `md2` or `md5`[3] [13], the content-encryption algorithm is DES in CBC mode, the digest-encryption algorithm is PKCS #1's `rsaEncryption` [14], and the key-encryption algorithm is PKCS #1's `rsaEncryption`. Under all those conditions, the doubly encrypted message digest and the encrypted content encryption key match the ones produced in PEM because of reasons similar to those given in Section 9.5, as well as the following:

1. The value input to the content-encryption algorithm in PEM is the same as in this standard. DES in CBC mode is the same as NIST/OIW's `desCBCwithPadding`[4].

2. The value input to the key-encryption algorithm in PEM is the same as in this standard (see Section 10.4). RSA public-key encryption in PEM is the same as PKCS #1's `rsaEncryption`.

3. The double-encryption process applied to the message digest in this standard and in PEM are the same.

The other parts of the signed-and-enveloped-data content type (certificates, algorithm identifiers, etc.) are easily translated to and from their corresponding PEM components.

12. Digested data content type

The digested-data content type consists of content of any type and a message digest of the content.

It is expected that the typical application of the digested-data content type will be to add integrity to content of the data content type, and that the result would become the content input to the enveloped-data content type.

The process by which digested-data is constructed involves the following steps:

1. A message digest is computed on the content with a message-digest algorithm.

2. The message-digest algorithm and the message digest are collected together with the content into a `DigestedData` value.

---

[3]Not yet registered.

[4]Not yet registered.

The process is reversed (i.e., the message digest is verified) by comparing the message digest to an independently computed message digest.

The digested-data content type shall have ASN.1 type `DigestedData`:

```
DigestedData ::= SEQUENCE {
  version Version,
  digestAlgorithm DigestAlgorithmIdentifier,
  contentInfo ContentInfo,
  digest Digest }

Digest ::= OCTET STRING
```

The fields of type `DigestedData` have the following meanings:

- `version` is the syntax version number. It shall be 0 for this version of the standard.
- `digestAlgorithm` identifies the message-digest algorithm (and any associated parameters) under which the content is digested. (The message-digesting process is the same as in Section 9 in the case when there are no authenticated attributes.)
- `contentInfo` is the content that is digested. It can be in of any of the defined content types.
- `digest` is the result of the message-digesting process.

Note. The fact that the `digestAlgorithm` field comes before the `contentInfo` field and the `digest` field comes after it makes it possible to process a `DigestedData` value in a single pass. (Single-pass processing is described in Section 5.)

13. Object identifiers

This standard defines six object identifiers: `pkcs-7`, `data`, `signedData`, `envelopedData`, `signedAndEnvelopedData`, and `digestedData`.

13.1 pkcs-7

The object identifier `pkcs-7` identifies this standard.

```
pkcs-7 OBJECT IDENTIFIER ::=
 { iso(1) member-body(2) US(840) rsadsi(113549) pkcs(1) 7 }
```

The pkcs-7 object identifier is intended to be used only in defining other object identifiers in this standard.

13.2 data

The object identifier data identifies the data content type defined in Section 8.

```
data OBJECT IDENTIFIER ::= { pkcs-7 1 }
```

The data object identifier is intended to be used in the contentType field of a value of type ContentInfo (see Section 7). The content field of that type, which has the content-type-specific syntax ANY DEFINED BY contentType, would have ASN.1 type Data (see Section 8) for this content type. This object identifier is also intended to be used in a PKCS #9 [16] content-type attribute.

13.3 signedData

The object identifier signedData identifies the signed-data content type defined in Section 9.

```
signedData OBJECT IDENTIFIER ::= { pkcs-7 2 }
```

The signedData object identifier is intended to be used in the contentType field of a value of type ContentInfo. The content field of that type, which has the content-type-specific syntax ANY DEFINED BY contentType, would have ASN.1 type SignedData (see Section 9) for this content type. This object identifier is also intended to be used in a PKCS #9 content-type attribute.

13.4 envelopedData

The object identifier envelopedData identifies the enveloped-data content type defined in Section 10.

```
envelopedData OBJECT IDENTIFIER ::= { pkcs-7 3 }
```

The envelopedData object identifier is intended to be used in the contentType field of a value of type ContentInfo. The content field of that type, which has the content-type-specific syntax ANY DEFINED BY contentType, would have ASN.1 type EnvelopedData (see Section 10) for this content type. This object identifier is also intended to be used in a PKCS #9 content-type attribute.

13.5 signedAndEnvelopedData

The object identifier `signedAndEnvelopedData` identifies the signed-and-enveloped-data content type defined in Section 11.

```
signedAndEnvelopedData OBJECT IDENTIFIER ::= { pkcs-7 4 }
```

The `signedAndEnvelopedData` object identifier is intended to be used in the `contentType` field of a value of type `ContentInfo`. The `content` field of that type, which has the content-type-specific syntax `ANY DEFINED BY contentType`, would have ASN.1 type `SignedAndEnvelopedData` (see Section 11) for this content type. This object identifier is also intended to be used in a PKCS #9 content-type attribute.

13.6 digestedData

The object identifier `digestedData` identifies the digested-data content type defined in Section 12.

```
digestedData OBJECT IDENTIFIER ::= { pkcs-7 5 }
```

The `digestedData` object identifier is intended to be used in the `contentType` field of a value of type `ContentInfo`. The `content` field of that type, which has the content-type-specific syntax `ANY DEFINED BY contentType`, would have ASN.1 type `DigestedData` (see Section 12) for this content type. This object identifier is also intended to be used in a PKCS #9 content-type attribute.